

## TECHNICAL FEATURES

<b>Type</b>	Hybrid pit platforms with stainless steel cell
<b>Material</b>	V1: Structure and painted sheet V2: Painted structure and stainless sheet V3: Completely stainless AISI 304
<b>Thickness of the sheet</b>	5 mm to 3000 kg 10 mm for platforms 6000 kg
<b>Installation</b>	Pit
<b>Dimensions</b>	From 1200 x 1000 to 2000 x 1500 mm, with 2 levers From 2500 x 1500 to 4000 x 1500 mm, with 3 levers
<b>Capacities</b>	300 kg to 6000 kg
<b>Height</b>	250 mm (to 1500 kg) except platforms 2000 x 500 (Height 290 mm) 290 mm (to 3000 kg) 400 mm (to 6000 kg)
<b>Cable length</b>	5 m

GIROPES



**BHE**

**HYBRID PIT PLATFORMS**

Stainless steel load cell



## OPTIONALS

### POSSIBLE ACCESSORIES

#### Support to weigh iron

Supports in U-shape to lean bars with metal steel shape

**Galvanized rollers** Rollers for the sliding of objects on the platform.

**Column for indicator** For 4 load cell platforms and hybrid scales. with base to fix on ground. 2 versions: painted steel and stainless steel. height: 1400 mm.

REFERENCE BHE			PAINTED STRUCTURE AND SHEET	PAINTED STRUCTURE AND STAINLESS STEEL SHEET	COMPLETELY STAINLESS STEEL AISI 304
Dimensions (mm)	Capacity (kg)	Readout (g)	# Code	# Code	# Code
1200 x 1000	300	100	170435	170438	170441
1200 x 1000	600	200	170436	170439	170442
1200 x 1000	1500	500	170437	170440	170443
1500 x 1250	600	200	170444	170447	170450
1500 x 1250	1500	500	170445	170448	170451
1500 x 1250	3000	1000	170446	170449	170452
1500 x 1500	600	200	170453	170456	170459
1500 x 1500	1500	500	170454	170457	170460
1500 x 1500	3000	1000	170455	170458	170461
2000 x 1500	1500	500	170462	170464	
2000 x 1500	3000	1000	170463	170465	
2500 x 1500	1500	500	170468		
2500 x 1500	3000	1000	170469		
3000 x 1500	1500	500	170471		
3000 x 1500	3000	1000	170472		
4000 x 1000	1500	500	170473		
4000 x 1000	3000	1000	170474		
4000 x 1500	1500	500	170475		
4000 x 1500	3000	1000	170476		
1500 x 1500	6000	2000	170477		
2000 x 1500	6000	2000	170478		
3000 x 1500	6000	2000	170479		
4000 x 1500	6000	2000	170480		


Note: The reference do not include the indicator

### REFERENCE APPROVAL & CALIBRATION

Description	
CE APPROVALS: From 3 kg to 15000 kg	-
ENAC CALIBRATIONS: From 30 kg to 15000 kg	-

### REFERENCE ACCESSORIES

Description	# Code
Supplement for ATEX cell with approval	240129
Additional metre of cable	240085



**OPTIONAL INDICATOR**  
» SERIE GI400-GI400i-GI410  
See page 58

**SOFTWARE**  
» For the management and control of production lines  
See page 65

Gs  
ONE

Gs  
PRO

## LOAD CELLS

### G1i

Bending beam load cell.  
Fully stainless steel.  
4000 divisions OIML R60 class C4.  
Hermetically sealed, fully in welded.  
Protection IP68