



GIROPES



BGU

## LIVESTOCK WEIGHING SCALE SLIDING DOORS

- Easy access. Low profile that allows an easy access to the animal
- Surface of the weighing on the embossed sheet and structure constructed completely in metal.
- Sliding doors in both ends to facilitate the opening and closing of the animals.
- It includes cross-passage panels to avoid confrontations among animals.

## TECHNICAL FEATURES

<b>Type</b>	Livestock weighing
<b>Material</b>	Steel S 275 JR
<b>Thickness of the sheet</b>	Tread plate 3/5 mm
<b>Installation</b>	Flat terrain
<b>Dimensions</b>	800 x 2500 mm to 1200 x 3000 mm
<b>Capacities</b>	1500 kg to 3000 kg
<b>Minimum height weight</b>	140 mm from the ground
<b>Maximum height of the scale</b>	1960 mm from the ground
<b>The covering height superficie</b>	800 mm
<b>Distance between top bars</b>	250-270 mm
<b>Data transmission</b>	Fix: by electrical cabling
<b>Support</b>	4 feet with rubber base
<b>Finished</b>	Polyurethane enamel two components Ral 5004 Ral 5004
<b>Cable length</b>	5 m

## REFERENCE BGU

				PAINTED		GALVANIZED	
Dimensions (mm)	Interior dimension (mm)	Capacity (kg)	Readout (g)	# Code		# Code	
800 x 2500	710	1500	500	170732		171229	
950 x 2500	860	1500	500	170733		171230	
950 x 3000	860	1500	500	170734		171231	
1200 x 2500	1110	1500	500	170735		171232	
1200 x 3000	1110	1500	500	170736		171233	
800 x 2500	710	3000	1000	170737		171234	
950 x 2500	860	3000	1000	170738		171235	
950 x 3000	860	3000	1000	170739		171236	
1200 x 2500	1110	3000	1000	170740		171237	
1200 x 3000	1110	3000	1000	170741		171238	

Note: The reference do not include the indicator

## REFERENCE APPROVAL & CALIBRATION

Description		
CE APPROVALS: From 3 kg to 15000 kg	-	
ENAC CALIBRATIONS: From 30 kg to 15000 kg	-	

## REFERENCE ACCESSORIES

Description	# Code
Additional metre of cable	240085



## OPTIONAL INDICATOR

» SERIE GI400-GI400i-GI410  
See page 58

## SOFTWARE

» For the management and control of production lines  
See page 65



## LOAD CELLS

**G3S- For painted platforms with capacity From 750 kg to 1500 kg.**

Shear beam load cell.  
Fully in steel alloy.  
3000 divisions OIML R60 class C3.  
Hermetically sealed, fully in welded.  
Protection IP68 (0, 30t – 5 t)