



**GIROPES**



**PA**

**AERIAL  
PLATFORM**

- Platform to be installed in three lines for aerial weighing track.
- It includes the fixing straps of the weighing track.

## TECHNICAL FEATURES

<b>Type</b>	Aerial Platforms
<b>Finished</b>	In stainless steel
<b>Thickness of the sheet</b>	15 mm
<b>Installation</b>	In lines of aerial track
<b>Dimensions</b>	<ul style="list-style-type: none"> <li>› PA 300 kg: length of the track 500 mm</li> <li>› PA 600 kg: length of the track 600 mm</li> <li>› PA 1000 kg: length of the track 800 mm</li> </ul>
<b>Capacities</b>	PA Version (2 load cells): 300 kg to 1000 kg
<b>Inside access</b>	The PA models allow access by removing the top sheet
<b>Cable length</b>	5 m (it includes a supplement of cable)
<b>Support</b>	It includes the fastening crosspieces of the track
<b>Crosspieces length</b>	400 mm
<b>Screws</b>	In stainless steel

## OPTIONALS

### POSSIBLE ACCESSORIES

**Stainless steel finish options** See page 50

### REFERENCE PA

Dimensions (mm)	Capacity (kg)	Readout (g)	COMPLETELY PAINTED LOAD CELL IN STAINLESS STEEL		COMPLETELY STAINLESS STEEL AISI 304 LOAD CELL IN STAINLESS STEEL	
			#	Code	#	Code
590 x 180 x 175	300	100	170007		170010	
770 x 180 x 175	600	200	170008		170011	
970 x 180 x 175	1000	500	170009		170012	

Note: The reference do not include the indicator

### REFERENCE APPROVAL & CALIBRATION

Description		
CE APPROVALS: From 3 kg to 15000 kg	-	
ENAC CALIBRATIONS: From 30 kg to 15000 kg	-	

### REFERENCE ACCESSORIES

Description	# Code
Additional metre of cable	240085



### OPTIONAL INDICATOR

» SERIE GI400-GI400i-GI410  
See page 58

### SOFTWARE

» For the management and control  
of production lines  
See page 65



## LOAD CELLS

### G5i

Bending beam load cell.  
Fully stainless steel.  
3000 divisions OIML R60 class C3.  
Hermetically sealed, fully in welded.  
Protection IP68